

DATASHEET



ASC2367

Aritech 2000 Series ceiling mount sounder/visual alarm

MAIN FEATURES

- Aritech 2000 Series ceiling mount sounder/visual alarm
- multi-tone with deep base

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	17 to 32 VDC
Current consumption	310 μ A (Quiescent @ 24 VDC)5.1 mA (Sounder ON @ 24 VDC)20 mA @ 0.5 Hz / 40 mA @ 1Hz (Beacon ON @ 24 VDC)

Inputs / outputs

Output level	97 $\pm$ 3 dB(A) @ 1 m @ 90° (Tone and voltage dependent)
Output level adjustment	8 dB

Physical characteristics

Cable size	0.28 mm ² to 2.5 mm ²
Colour	Red
Physical dimensions	100 x 104 mm (Ø x H)
Net weight	345 g
Mounting type	Ceiling mount
Mounting position	Base
Mounting height	Up to 3 m
Mounting base	Deep
Material	High impact polycarbonate

Environmental characteristics

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	5 to 95% noncondensing

ASC2367

TECHNICAL SPECIFICATIONS

Environment	Outdoor
IP rating	IP33C (Deep base IP65)
Other characteristics	
Compatibility	Aritech 2000 series systems
Switch on surge	<1.2 mA
Frequency	400 to 2850 Hz (tone dependent)
Selectable tones	32
Synchronization	Automatic
Rating	C-3-9
Floor coverage	63 m²
Flash frequency	0.5 or 1 Hz
Vandal proof	No
Compliance	CE, REACH, RoHS 2, WEEE
Certification	EN54-23, EN54-3
Category	Reference
Notification device	AS36RIM