

DATASHEET

ASC366W

Conventional Ceiling Mount Sounder/VAD

MAIN FEATURES

- Conventional Ceiling Mount Sounder/VAD
- Multi Tone
- Shallow Base - Red Flash



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	17 to 60 VDC
Current consumption	Beacon: 20 mA @ 0.5 Hz 40mA @ 1 HzSounder: 5.1 mA

Inputs / outputs

Output level	85 to 97 dB(A) (Sound output @ 1 m, tone dependant)Continuous operation
--------------	---

Physical characteristics

Colour	Red
Physical dimensions	100 x 94 mm (Ø x D)
Net weight	215 g
Material	High impact polycarbonate
Mounting position	Ceiling
Mounting height	up to 3 m

Environmental characteristics

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor
IP rating	IP21

Other characteristics

Line monitoring	Polarised input
-----------------	-----------------

ASC366W

TECHNICAL SPECIFICATIONS

Selectable tones

Synchronization

Certification

Light coverage

Floor coverage

32

Phased start (Automatic)

EN54-23, EN54-3

C-3-8.9

up to 8.9 m diameter