

DATASHEET

ASC366

Conventional Ceiling Mount Sounder/VAD

MAIN FEATURES

- Conventional Ceiling Mount Sounder/VAD
- Multi Tone
- Shallow Base - Red Flash



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	17 to 60 VDC
Current consumption	5.1 mA (Sounder) 20 mA @ 0.5 Hz, 40 mA @ 1 Hz (Beacon)

Inputs / outputs

Output level	85 to 97 dB(A) @ 1 m (tone dependant) Continuous operation
--------------	--

Physical characteristics

Colour	Red
Physical dimensions	100 x 94 (Ø x D)
Net weight	215 g
Mounting type	Base mount
Mounting position	Ceiling
Mounting height	up to 3 m
Mounting base	Shallow
Material	High impact polycarbonate

Environmental characteristics

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor
IP rating	IP21

Other characteristics

ASC366

TECHNICAL SPECIFICATIONS

Line monitoring
Selectable tones
Synchronization
Rating
Floor coverage
Flash frequency
Texture
Compliance
Certification
Voluntary marks (all languages)
Category
Notification device

Polarised input
32
Automatic, Phased start
C-3-8.9
up to 40 m²
0.5 Hz
Smooth
CE, REACH, RoHS 3, WEEE
EN54-23, EN54-3
BOSEC
Reference
ASC366W