

DATASHEET

ASC367

Conventional Ceiling Mount Sounder/VAD

MAIN FEATURES

- Conventional Ceiling Mount Sounder/VAD
- Multi Tone
- Deep Base - Red Flash



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	17 to 60 VDC
Current consumption	Beacon: 20 mA @ 0.5 Hz, 40 mA @ 1 Hz Sounder: 5.1 mA

Inputs / outputs

Output level	Continuous operation 85 to 97 dB(A) (Sound output @ 1 m, tone dependant)
--------------	--

Physical characteristics

Colour	Red
Physical dimensions	97.5 x 117 mm (Ø x D)
Net weight	215 g
Mounting type	Base mount
Mounting position	Ceiling
Mounting height	up to 3 m
Mounting base	Deep
Material	High impact polycarbonate

Environmental characteristics

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor, Outdoor
IP rating	IP65

Other characteristics

ASC367

TECHNICAL SPECIFICATIONS

Line monitoring

Selectable tones

Synchronization

Rating

Floor coverage

Flash frequency

Texture

Compliance

Certification

Voluntary marks (all languages)

Polarised input

32

Phased start (Automatic)

C-3-8.9

up to 40 m²

0.5 Hz

Smooth

CE, REACH, RoHS 3, WEEE

EN54-23, EN54-3

BOSEC