

DATASHEET

ASW367

Conventional wall mount sounder/VAD

MAIN FEATURES

- Conventional wall mount sounder/VAD
- multi-tone
- deep base
- red flash

TECHNICAL SPECIFICATIONS

Power supply

Power supply type	VDC
Operating voltage	17 to 60 VDC
Current consumption	5.1 mA (sounder)20 mA @ 0.5 Hz (VAD)

Inputs / outputs

Output level	85 to 97dB(A) @ 1 m (tone dependant)
--------------	--------------------------------------

Physical characteristics

Colour	Red
Physical dimensions	97.5 x 117 mm (Ø x D)
Net weight	215 g
Mounting type	Base mount
Mounting position	Wall
Mounting height	up to 2.4 m
Mounting base	Deep
Material	High impact polycarbonate

Environmental characteristics

Operating temperature	-10 to +55°C
Relative humidity	5 to 95% noncondensing
Environment	Indoor, Outdoor
IP rating	IP65

ASW367

TECHNICAL SPECIFICATIONS

Other characteristics

Compatibility	All conventional notification circuits
Line monitoring	Polarised input
Selectable tones	32
Synchronization	Phased start
Rating	W-2.4-7.5
Floor coverage	56.25 m ²
Flash frequency	0.5 Hz
Texture	Smooth
Vandal proof	No
Compliance	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54-3
Voluntary marks (all languages)	BOSEC
Category	Reference
Notification device	ASW366