

DATASHEET

ASW377

Sounder/Beacon

MAIN FEATURES

- Sounder/Beacon
- Multi Tone
- High Output
- IP66
- Red Flash

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	17 to 60 VDC
Current consumption	10 to 50 mA @ 24 VDC Sounder (tone dependant) 65 mA @ 0.5 Hz (Beacon)

Inputs / outputs

Output level	104 to 116dB(A) @ 24 VDC (Sound output @ 1 m, tone dependant) Continuous operation
--------------	--

Physical characteristics

Colour	Red
Physical dimensions	166 x 189 x 149.5 mm (W x H x D)
Net weight	1.2 kg
Mounting type	Wall mount
Mounting position	Wall
Mounting height	up to 2.4 m
Material	High impact polycarbonate

Environmental characteristics

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Outdoor
IP rating	IP66

Other characteristics

ASW377

TECHNICAL SPECIFICATIONS

Line monitoring

Selectable tones

Synchronization

Rating

Floor coverage

Flash frequency

Texture

Compliance

Certification

Voluntary marks (all languages)

Polarised input

64

Phased start, Automatic synchronisation

W-2.4-7.5

up to 56 m²

0.5 Hz

Smooth

CE, REACH, RoHS 3, WEEE

EN54-23, EN54-3

BOSEC