

DATASHEET

ATS1136

Advisor Advanced Secure Mifare keypad

MAIN FEATURES

- Advisor Advanced Secure Mifare keypad



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	8.5 to 14 VDC
Power supply type	12 VDC
Current consumption	30 mA normal operation 280 mA max.

Inputs / outputs

Inputs	1
Input type	Request to Exit
Outputs	1
Output type	Open collector, 15 V max. at 50 mA max.

Physical characteristics

Physical dimensions	200 x 90 x 24 mm
Net weight	350 g
Colour	White
Mounting type	Surface mount

Environmental characteristics

Operating temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP30

Other characteristics

ATS1136

TECHNICAL SPECIFICATIONS

User interface	2 x 16 Char LCD, Touch Buttons
Product line	Advisor Advanced
Status LEDs	2
Integrated reader	Secure MIFARE
Function keys	3
Supported card types	Mifare Classic 7 Byte UID, MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	DIP Switches
Supported cable type	WCAT 52/54 or equivalent
Communication type	Wired
Reading distance	Up to 5 cm
Form factor	Horizontal
EN50131 grade	Grade 3
Compliance	CE, RoHS
Certification	VdS