

DATASHEET

ATS1180

Secure MIFARE DESFire EV1/EV2 card reader with output and RTE input in slim design

MAIN FEATURES

- Secure MIFARE DESFire EV1/EV2 card reader with output and RTE input in slim design



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	10.8 to 30 VDC
Current consumption	50 mA @13.8 VDC normal 80 mA @13.8 VDC max.

Inputs / outputs

Inputs	Request to exit
Outputs	1 Open Collector (10 mA)

Physical characteristics

Physical dimensions	140 x 44 x 20 mm
Net weight	240 g
Shipping weight	275 g
Colour	Black
Material	Plastic
Mounting Type	Surface mount

Environmental characteristics

Reader operating-transmitting frequency	13.56 MHz
Operating temperature	-40 to +55°C
Storage temperature	-40 to +55°C
Relative humidity	<95%, noncondensing
Environment	Indoor, Outdoor
IP rating	IP67IK09

ATS1180

TECHNICAL SPECIFICATIONS

Other characteristics

Reading distance	Secure: max. 2 cm Unsecure: max. 5 cm
Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes
Addressing type	Card Addressing
No. of LEDs	3
Reader type	Smart Card
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (custom data)
No. of Mifare bytes CSN	4 Bytes (non-unique), 4 Bytes (S50), 7 Bytes (S50), 7 Bytes (S70)
Interface	ATS RS-485
Connector type	Pigtail
Pigtail length	2 m
Pry-off tamper	Yes
PIN keypad	No
Form factor	Slimline
Compliance	CE
Certification	VdS