

DATASHEET

ATS1190X4

4 pack ATS1190 Smart card reader with 2.5 m cable

MAIN FEATURES

- 4 pack ATS1190 Smart card reader with 2.5 m cable

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	9 to 14 VDC
Current consumption	25 mA typical 80 mA max.

Inputs / outputs

Inputs	Request to exit
Outputs	1 Open Collector (25 mA)

Physical characteristics

Physical dimensions	36 x 110 x 20 mm
Net weight	200g (per reader)
Colour	White
Material	Plastic
Mounting Type	Surface mount

Environmental characteristics

Reader operating-transmitting frequency	125 KHz
Operating temperature	-35 to +66°C
Environment	Indoor
IP rating	IP54

Other characteristics

Reading distance	6 to 8 cm
Max. reader distance to panel	1.5 km

ATS1190X4

TECHNICAL SPECIFICATIONS

Supported card types
Addressing type
No. of LEDs
No. of covers included
Reader accessory
Reader type
Supported technology 125 kHz
Interface
Connector type
Pigtail length
Pry-off tamper
PIN keypad
Vandal proof

HiTag2
Card Addressing, Keypad Addressing, Software Addressing
Tricolor
4, White
Optional Color Covers
Proximity, Smart Card
HiTag 2
ATS RS-485, Wiegand
Pigtail
250
Yes
No
No