

DATASHEET

ATS1192X4

4 pack ATS1192 Heavy-duty smart card reader with 2.5 m cable

MAIN FEATURES

- 4 pack ATS1192 Heavy-duty smart card reader with 2.5 m cable

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	9 to 14 VDC
Current consumption	25 mA typical 80 mA max.

Inputs / outputs

Inputs	Request to exit
Outputs	1 Open Collector (25 mA)

Physical characteristics

Physical dimensions	42 x 150 x 16 mm
Net weight	250g (per reader)
Colour	Dark grey
Mounting Type	Surface mount

Environmental characteristics

Reader operating-transmitting frequency	125 KHz
Operating temperature	-35 to +66°C
Environment	Outdoor
IP rating	IP54

Other characteristics

Reading distance	6 to 10 cm
Max. reader distance to panel	1.5 km
Supported card types	HiTag2

ATS1192X4

TECHNICAL SPECIFICATIONS

Addressing type	Card Addressing, Keypad Addressing, Software Addressing
No. of LEDs	Bicolor
Reader type	Proximity, Smart Card
Supported technology	125 kHz
Interface	HiTag 2
Connector type	ATS RS-485, Wiegand
Pigtail length	Pigtail
Pry-off tamper	250
PIN keypad	Yes
	No