

DATASHEET

ATS1211E

8 -16 zones DGP expander

MAIN FEATURES

- 8 -16 zones DGP expander
- no PSU
- Metal housing
- EN50131 Grade 3 Class II

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	10.5 to 13.8 VDC
Current consumption	53 mA max.
Integrated power supply	No

Inputs / outputs

Type of outputs	Open Collector
-----------------	----------------

Physical characteristics

Physical dimensions	165 x 125 x 36mm
Net weight	790 gr
Material	Steel (painted)
Housing	Metal

Environmental characteristics

Operating temperature	-10 to +55°C
Relative humidity	95% noncondensing
Environment	EN50130-5
IP rating	IP30

Other characteristics

Expander type	Input expander
Product line	Advisor Advanced, ATS Master, Axon
Connection type	Databus connection

ATS1211E

TECHNICAL SPECIFICATIONS

Compatibility	Advisor Advanced, Advisor Master or Axon
Max. distance from panel	1.5 km
Max. per panel	15 / 30 (depending on panel type)
Specified cable	WCAT52 / WCAT54 or equivalent
Addressing	DIP Switches
End-of-line resistor	Selectable
Total	8
Onboard	8
Compliance	CE
Certification	EN50131 Grade 3, VdS