

## DATASHEET

### BS133N

Battery

#### MAIN FEATURES

- Battery
- 12 V
- 65 Ah



#### TECHNICAL SPECIFICATIONS

##### Power supply

|                         |                   |
|-------------------------|-------------------|
| Nominal voltage         | 12 V              |
| Max. charge voltage     | 13.8 VDC at +20°C |
| Max. charge current     | 19.5A             |
| Max. discharge current  | 325 A             |
| Charging temperature    | 0 to +40°C        |
| Discharging temperature | -15 to +50°C      |

##### Physical characteristics

|                     |                    |
|---------------------|--------------------|
| Physical dimensions | 350 x 166 x 174 mm |
| Net weight          | 23.0 kg            |
| Shipping weight     | 23.0 kg            |
| Material            | ABS                |

##### Environmental characteristics

|                       |              |
|-----------------------|--------------|
| Operating temperature | 0 to +40°C   |
| Storage temperature   | -15 to +50°C |

##### Other characteristics

|                             |                          |
|-----------------------------|--------------------------|
| Product type                | Sealed lead acid battery |
| Nominal capacity            | 65 Ah                    |
| Internal approx. resistance | 10 mOhm                  |
| Terminal type               | MS bolt & nuts           |

## BS133N

### TECHNICAL SPECIFICATIONS

---

Fire retardant  
Compliance  
Certification

No  
CE, RoHS 2, WEEE  
VdS