

## DATASHEET

# DC138S60

Industrial flush mount contact for steel door

## MAIN FEATURES

- Industrial flush mount contact for steel door
- high security grade 3
- white
- 6m cable

## TECHNICAL SPECIFICATIONS

### Power supply

|                   |                                           |
|-------------------|-------------------------------------------|
| Operating voltage | max. 40 V (permissible operating voltage) |
| Voltage           | max. 100 VDC                              |
| Contact power     | max. 6 W or 6 VA                          |
| Switching current | max. 500mA                                |

### Inputs / outputs

|                             |                                            |
|-----------------------------|--------------------------------------------|
| Contact type                | 1 pin NC contact                           |
| Wired-wireless              | Wired                                      |
| Contact resistance          | max. 0.15 Ohm                              |
| Dimensions contact / sensor | 8 x 32 mm with installation flange EF 8/20 |

### Physical characteristics

|                     |                                   |
|---------------------|-----------------------------------|
| Physical dimensions | Ø 3.2 mm x 6 m (cable dimensions) |
| Dimensions magnet   | 6 x 19 mm                         |
| Colour              | White                             |
| Material            | ABS                               |

### Environmental characteristics

|                       |             |
|-----------------------|-------------|
| Operating gap         | 12 mm       |
| Operating temperature | -25 to 70°C |
| IP rating             | IP67class 3 |

### Other characteristics

## DC138S60

### TECHNICAL SPECIFICATIONS

---

Application type

Connectivity

EN50131 grade

Certification

Recessed mount

LIYY 4 x 0.14 mm Cu tin-plated

Grade 3

VdS