

DATASHEET

DD669AM

360° ceiling mount

MAIN FEATURES

- 360° ceiling mount
- Dual motion sensor
- 20 m
- anti-mask

TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	9 to 15 VDC
Power supply type	12 VDC
Power supply value	9 to 15 VDC (12 V nominal)
Current consumption	19 mA

Inputs / outputs

Max. microwave output (at 1m)	0.003 μ W/cm ²
Wired-wireless	Wired
Alarm relay characteristic	NC when energised
Tamper relay characteristic	NC when cover closed
Anti mask relay characteristic	NC, 80 mA 30 VDC, Form A
Relay configuration	Isolated or 4k7 EOL

Physical characteristics

Physical dimensions	138 x 92 mm
Colour	White
Mounting height	2.5 to 5 m

Environmental characteristics

Operating temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor

DD669AM

TECHNICAL SPECIFICATIONS

Other characteristics

Technology	Dual
Application type	Ceiling mount
Anti masking	Yes
Pet immune	No
Camera	No
Pry-off tamper kit	On board
Max. detection range	20 m
Detection range	20 m / 12 m
No. of curtains	18
Coverage (field of view)	360° or 180°
Microwave frequency (nom.)	5.8 GHz
Undercrawl protection	Yes
Target speed range	0.2 to 3.0 m/s
Alarm memory	Yes
Alarm time	3 s
Peak-to-peak ripple immunity	2 V (at 12 VDC)
Remote control lines	Day/Night, Walk test
EN50131 grade	Grade 3
Certification	VdS