

## DATASHEET

## FAC355

Conventional VAD

## MAIN FEATURES

- Conventional VAD
- Deep Base
- Ceiling Mount - Red Flash



## TECHNICAL SPECIFICATIONS

## Power supply

|                     |                               |
|---------------------|-------------------------------|
| Operating voltage   | 17 to 60 VDC                  |
| Current consumption | 20 mA @ 0.5 Hz / 40 mA @ 1 Hz |

## Inputs / outputs

|              |                      |
|--------------|----------------------|
| Output level | Continuous operation |
|--------------|----------------------|

## Physical characteristics

|                     |                           |
|---------------------|---------------------------|
| Colour              | Red                       |
| Physical dimensions | 100 x 104 mm (Ø x D)      |
| Net weight          | 250 g                     |
| Mounting type       | Ceiling mount             |
| Mounting height     | up to 3 m                 |
| Material            | High impact polycarbonate |

## Environmental characteristics

|                       |                        |
|-----------------------|------------------------|
| Operating temperature | -25 to +70°C           |
| Relative humidity     | 5 to 95% noncondensing |
| Environment           | Indoor, Outdoor        |
| IP rating             | IP65                   |

## Other characteristics

|                 |                          |
|-----------------|--------------------------|
| Line monitoring | Polarised input          |
| Synchronization | Phased start (Automatic) |

## FAC355

### TECHNICAL SPECIFICATIONS

---

Floor coverage  
Flash frequency  
Certification  
Light coverage

up to 8.9 m diameter  
0.5 or 1 Hz30 or 60 flashes/min  
EN54-23  
C-3-8.9