

DATASHEET

NC-MCS22-0-0

Intelligent conventional recess mount manual call point FÜSTELVEZETÉS

MAIN FEATURES

- Intelligent conventional recess mount manual call point FÜSTELVEZETÉS
- 0 Ω (orange)



TECHNICAL SPECIFICATIONS

Power supply

Power supply type	VDC
Operating voltage	10 to 24 VDC
Current consumption	0 mA (Standby)

Inputs / outputs

Zone length	<2 km, CIE specific
Output quantity	2
Output type and rating	1 x NO resistor limited, 1 x change over relay 1 A @ 24 VDC

Physical characteristics

Physical dimensions	87 x 87 x 26 mm (W x H x D)
Net weight	101 g
Colour	Orange (RAL 2008)
Mounting type	Back box, Wall mount
Material (body)	Flame retardant ABS

Environmental characteristics

Operating temperature	-10 to +55°C
Storage temperature	-25 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP41

NC-MCS22-0-0

TECHNICAL SPECIFICATIONS

Other characteristics

Status indication	Alarm flag
Compatibility	Conventional alarm systems
Connectivity	Hardwired contacts
Cable specification	0.404 to 2.05 mm (0.13 to 3.31 mm ²)
No. of cable cores	2
Terminals	7
Detection principle	Manual activation
Monitoring	Activated, Off
Coverage area	Region specific
Response time	< 3 s
Installation height	Determined by local regulation
Functional marking	FÜSTELVEZETÉS
Vandal proof	No
Compliance	CE, REACH, RoHS 3, WEEE
Certification	CE
Product series (all languages)	NC-Series
Category	Reference
Detection device	N-MC-BB-0