

DATASHEET

RF430I4

Wireless Mini Outdoor PIR 433-63

MAIN FEATURES

- Wireless Mini Outdoor PIR 433-63



TECHNICAL SPECIFICATIONS

Power supply

Operating voltage	2 x 3 V, CR123
Current consumption	50 µA
Battery lifetime	3 years

Inputs / outputs

Wired-wireless	Wireless
Wireless frequency	433 MHz legacy

Physical characteristics

Mounting height	Variable up to 6 m / Optimum height 3 m for full range
Physical dimensions	70 x 120 x 75 mm
Net weight	218 g
Shipping weight	351 g
Colour	Bronze
Material	High impact ABS plastic with HDPE cover, UV stabilized

Environmental characteristics

Operating temperature	-25 to +65°C
Environment	Outdoor
IP rating	IP65

Other characteristics

Technology	PIR
------------	-----

RF430I4

TECHNICAL SPECIFICATIONS

Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	On board
Fresnel lens	20 zones for each detection element, which can be masked with the curtain sliders
Pulse count	1 or 2
LED	Red: Walk test indicator
Max. detection range	15 m
Coverage (field of view)	14° to 70° detection angle, 15 m x 13 m coverage max.
Vertical optical axis adjustment	45° tilt
Horizontal optical axis adjustment	90° pan
Undercrawl protection	No
Batteries	CR123
Compliance	CE