

DATASHEET

S20-2SLC-20

SFP-Port 100Base-FX Mini GBIC Transceiver
(1310nm) - 20Km - SM

MAIN FEATURES

- SFP-Port 100Base-FX Mini GBIC Transceiver (1310nm) - 20Km - SM

TECHNICAL SPECIFICATIONS

Power supply

Power (dBm)	-15 ~ -8
Power budget	19
Operating voltage	3.3 VDC
Optical output power	Min. : -15dBm, Type : -, Max. : -8dBm

Physical characteristics

Physical dimensions	59 x 15 x 12.4 mm (W x D x H) 2.20 x 0.59 x 0.49 in. (W x D x H)
Net weight	18 g 0.6 oz

Environmental characteristics

Operating temperature	0 to +50°C
Storage temperature	-40 to +85°C
Relative humidity	5% to 95% noncondensing

Other characteristics

Category	SFP
Port type	Single Mode
No. of fibers	2
Port speed	Fast
Wavelength	1310 nm
Maximum distance	20 km
Number of fibers	2

S20-2SLC-20

TECHNICAL SPECIFICATIONS

Fiber type	Single-Mode
Connector	LC
Max. distance	20km
TX / RX wavelenght	1310nm / 1310nm
PHY type	100Base-LX
RX Sen. (dBm)	-34
Reliability (MTBF)	>50, 000 hrs @ 25° C
AS/NZS CISPR 22	2006
EMI	EN 55022 CLASS A:2006+A1 : 2007 / EN61000-3-2:2006 / EN61000-3-3: 1995+A1:2001+A2:2005
Receiver	-34dBm