

DATASHEET

SC-33-0120-0001-99

SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)

MAIN FEATURES

- SmartCell Red Sounder and Ceiling-Beacon (VAD White Flash)



TECHNICAL SPECIFICATIONS

Inputs / outputs

Wireless frequency	868 MHz
Output level	92 dB(A) at 1 m max.
Output level adjustment	High or low

Physical characteristics

Colour	white flash
Physical dimensions	110 x 79 mm (Ø x D)
Net weight	0.2 kg
Mounting type	Ceiling mount
Mounting position	Ceiling

Environmental characteristics

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
IP rating	Type B: for indoor/outdoor use (IP33)

Other characteristics

Compatibility	SmartCell, Excellence Gateway
Batteries	3 x3.6 V lithium thionyl chloride batteries.Fanso: ER14505MHCB: ER14505M (HCB-JS-TZ-02-547)
Selectable tones	32
Rating	C-3-12

SC-33-0120-0001-99

TECHNICAL SPECIFICATIONS

Flash frequency

0.5 Hz (1 flash, every 2 seconds)

Compliance

CE

Certification

CPR

Standards

EN54-3EN54-13EN54-23EN54-25