

## DATASHEET

# SC-51-0300-0001-04

SmartCell Hausalarm Manual Call Point

## MAIN FEATURES

- SmartCell Hausalarm Manual Call Point



## TECHNICAL SPECIFICATIONS

### Inputs / outputs

|                    |         |
|--------------------|---------|
| Wireless frequency | 868 MHz |
|--------------------|---------|

### Physical characteristics

|                     |                             |
|---------------------|-----------------------------|
| Physical dimensions | 92 x 97 x 47 mm (W x H x D) |
| Net weight          | 0.2 kg                      |
| Colour              | Blue (RAL 5005)             |
| Mounting type       | Wall mount                  |

### Environmental characteristics

|                       |                                  |
|-----------------------|----------------------------------|
| Operating temperature | -10 to +55°C                     |
| Storage temperature   | -10 to +55°C (without batteries) |
| Relative humidity     | 95% noncondensing max.           |
| Environment           | Indoor                           |

### Other characteristics

|                     |                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------|
| Status indication   | LED                                                                                          |
| Compatibility       | SmartCell, Excellence Gateway                                                                |
| Batteries           | 2 x 3.6 V lithium thionyl chloride batteries.Fanso: ER14505MHCB: ER14505M (HCB-JS-TZ-02-547) |
| Compliance          | CE                                                                                           |
| Certification       | CPR                                                                                          |
| Certification marks | EN54-25                                                                                      |
| Standards           | EN54-25                                                                                      |