

DATASHEET

TCC-0007

IS sounder/beacon

MAIN FEATURES

- IS sounder/beacon
- 24 V
- amber lens

TECHNICAL SPECIFICATIONS

Power supply

Power supply type	24 VDC
Operating voltage	24 VDC
Current consumption	33 mA

Inputs / outputs

Output level	>105 dB(A)
--------------	------------

Physical characteristics

Colour	Amber
Net weight	0.33 kg
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Deep

Environmental characteristics

Operating temperature	-40 to +55°C
Relative humidity	>90% at 20°C
Hazardous environment rating	Intrinsically safe - Zones 0, 1, 2, 20, 21 & 22
IP rating	IP66

Other characteristics

Compatibility	TCC-0012, GBX370
System support	Conventional intrinsically safe systems

TCC-0007

TECHNICAL SPECIFICATIONS

Selectable tones	32
No. of stages	2
Flash frequency	1 Hz or constant (ON)
Texture	Smooth
Vandal proof	No
Compliance	CE, REACH, RoHS 3, WEEE
Certification	CENELEC/ATEX, CPR
Standards	ATEX (EMT17ATEX0012X) IECEx (EMT 17.0005X)EN54-3