

DATASHEET

TESTIFIRE-XTR2-6M

All-in-one connected smoke/heat detector test kit to 6 m

MAIN FEATURES

- All-in-one connected smoke/heat detector test kit to 6 m



TECHNICAL SPECIFICATIONS

Power supply

Power supply type	Batteries
Operating voltage	10.8 V (35.1 wh / 3250 mAh)
Current consumption	< 0.5 A rms (smoke testing) 4 to 6 A rms (heat testing)
Battery type	Lithium Ion
Charging	USB-C connection to charging cradle

Physical characteristics

Physical dimensions	406 x 156 x 150 mm
Net weight	1.25 kg
Shipping weight	2.39 kg
Colour	Black, Grey

Environmental characteristics

Operating temperature	5 to 45°C (41 to 113°F) - Head unit 5 to 40°C (41 to 104°F) - Charger cradle
Storage temperature	-10 to 50°C (14 to 122°F)
Relative humidity	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Other characteristics

Stimulus type	Cartridge
Vandal proof	No
Compliance	CE, REACH, RoHS 3, WEEE
Certification	CE

TESTIFIRE-XTR2-6M

TECHNICAL SPECIFICATIONS

Product brand	testifire
Carbon Monoxide	No
Heat	Yes
Smoke	Yes
Category	Reference
Test Equipment	ET011