

## DATASHEET

## VV602-PLUS

Seismic detector for ATMs and night safe deposit boxes

## MAIN FEATURES

- Seismic detector for ATMs and night safe deposit boxes



## TECHNICAL SPECIFICATIONS

## Power supply

|                     |                  |
|---------------------|------------------|
| Low voltage alarm   | 7.5 V            |
| Power supply value  | 9 to 15 VDC      |
| Current consumption | 8.6 mA (nominal) |

## Inputs / outputs

|               |                                                        |
|---------------|--------------------------------------------------------|
| Alarm contact | Form A solid state relay, max series resistance 35 ohm |
| Test output   | Yes                                                    |

## Physical characteristics

|                     |                              |
|---------------------|------------------------------|
| Physical dimensions | 81 x 101 x 28 mm (W x H x D) |
| Net weight          | 380 g                        |
| Colour              | Grey (RAL 7035)              |

## Environmental characteristics

|                       |                        |
|-----------------------|------------------------|
| Operating temperature | -20 to +55°C           |
| Relative humidity     | 0 to 90% noncondensing |
| IP rating             | IP30                   |

## Other characteristics

|                   |                                                                  |
|-------------------|------------------------------------------------------------------|
| Application type  | ATM, Night safe deposit boxes                                    |
| Tamper protection | Temperature 84°C, drill shield, opening contact, pry-off contact |
| Alarm indication  | LED-indication screw no. 3                                       |
| Range             | 3 to 14 m radius                                                 |

## VV602-PLUS

### TECHNICAL SPECIFICATIONS

---

Sensitivity adjustment  
Certification

5 steps of approx. 6 dB each  
VdS